

# VARNISHING AND AUXILIARY PRODUCTS



# **AQUA TIME**

#### **RETARDANT ADDITIVE**

Retarder solution recommended for water-based varnishes. AQUA TIME is particularly recommended for very dry, warm environments. The product reduces the likelihood of blotches or overlaps when coating.

#### **TECHNICAL CHARACTERISTICS:**

- Slows varnish drying times considerably
- Suitable for summer weather conditions
- Compatible with all Adesiv water-based varnishes
- Recommended thinning: max 5%

## WHERE THE VARNISH WITH ADDED AQUA-TIME CAN BE APPLIED:

- Warm environments
- Large surfaces
- On particularly absorbent wood

## **SPECIFIC CHARACTERISTICS (normal conditions):**

Appearance:	Transparent liquid
Viscosity, Ford 4 at 20 °C (seconds):	11 - 12
Storage (months): temperature between +5°C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	500 ml bottles
Usage limitations:	Always use suitable personal protective equipment Always consult the technical and safety information sheets Frost sensitive.

#### APPLICATION:

Add a maximum of 5 % of AQUA TIME to a water-based varnish and mix thoroughly before use. Apply the paint or varnish in accordance with the product technical data sheet. Always consult the product's technical and safety information sheets before use.

# **HAZARD PICTOGRAMS:**

-- -- --