



ADE-GRAB 30

FAST-SETTING HYBRID ADHESIVE

Fast-setting hybrid adhesive based on silane polymers, ideal for fixing a variety of materials such as skirting boards, solid wood elements, wall panels, vinyl flooring, decorative elements and laminate accessories. ADE-GRAB 30 can also be used for filling and sealing expansion and connection joints in buildings.

TECHNICAL CHARACTERISTICS:

- Quick-setting monocomponent
- Colour White
- Adheres to multiple surfaces
- Adhesive and sealant
- Elastic and tough
- Overpaintable (after application test)

WHERE IT CAN BE APPLIED:

- Wood or PVC edging or skirting boards on absorbent surfaces
- Decorative elements and accessories for laminates (after application test)
- Universal bonding of solid wood elements
- Bonding wood panelling to walls
- Sealing of joints in buildings

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Clear paste
Density:	1.36 g/cm ³
Usage temperature (°C):	+5 - +30
Open time (minutes):	25 - 30
Shore A hardness:	30
Final setting (after 24 hours):	3 mm approx. (time until product is ready for walking on and final setting times vary depending on weather conditions and thickness of applied layer)
Application/Equipment:	Caulking gun - 280/310 ml
Equipment cleaning:	water, before the product sets
Product removal:	GR7 Solvent
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	290 ml Cartridges
Usage limitations:	It is recommended to set the product at a temperature of at least 15 °C before use. Do not use for glass sealing and applications in combination with natural stone. Always use adequate personal protective equipment. Always consult the technical and safety data sheets

SURFACE PREPARATION:

Ensure that the surface to be bonded is clean and free of release agents such as oil, grease, dust and old, incompatible adhesives. The product offers excellent adhesion even on damp or slightly damp surfaces after an application test.

APPLICATION:

The product is ready for use. Insert the 290 ml packaging into its applicator. Carefully cut the cartridge at the end and after inserting the appropriate extrusion nozzle apply the product directly onto one of the two surfaces in dots or continuous beads in the case of sealing. Thoroughly press the product onto the surface so the space underneath is completely filled with adhesive. Remove any glue residue with a cloth before the product has set, and in any case, before 5 minutes have elapsed. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

HAZARD PICTOGRAMS:

-- -- --