



DILUENTE MB

SOLVENT-BASED RETARDANT FOR PAINT

Retardant solution suitable for solvent-based paints. DILUENTE MB thinner is particularly useful when working in very hot and dry environments. The product reduces the likelihood of blotches or overlaps when varnishing.

TECHNICAL CHARACTERISTICS:

- Slows varnish drying times considerably
- Suitable for summer weather conditions
- Compatible with all Adesiv solvent-based varnishes
- Recommended thinning: max 3-5%

WHERE VARNISH WITH ADDED DILUENTE MB CAN BE APPLIED:

- Warm rooms during summer months
- Large surfaces
- On particularly absorbent wood

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Transparent liquid
Viscosity, Ford 4 at 20 °C (seconds):	11 - 12
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in accordance with local and national legislation
Packaging:	5-litre containers
Usage limitations:	Flammable product Always use suitable personal protective equipment

APPLICATION:

After catalysis, add a maximum of 5% of DILUENTE MB to a solvent-based varnish and mix thoroughly before use. Apply the paint or varnish in accordance with the product technical data sheet. Always consult the technical and safety data sheet of the product before use.

HAZARD PICTOGRAMS:

