



PAVICERA SO

SPECIAL SOLID WAX FOR PARQUET FLOORING

Special wax solution for treating precious wooden floors to be polished.

TECHNICAL CHARACTERISTICS:

- Easy to apply
- Natural effect

WHERE IT CAN BE APPLIED:

- Smoothed wood flooring
- Wooden furniture or features

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Creamy emulsion
Viscosity:	N. D.
Yield (g/m ²):	Depends on the absorbent base
Drying time (hours)	3 - 4
Usage temperature (°C):	+ 10 - +25
Application/Equipment:	Clean cloth, buffer
Storage (months): temperature of between +5°C and +25°C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	5-litre containers
Usage limitations:	Inflammable product. Do not apply in damp environments. Always use adequate individual protection devices. Allow the product to reach room temperature of 20°C before application.

PREPARING THE SURFACE

Clean the surface with DECERLEGNO (see technical data sheet) and leave to dry completely.

APPLICATION

Apply a thin layer of PAVICERA SO with a cloth, leave to dry, and polish manually with a cloth or buffing machine. Several coats can be applied. Apply and polish with a soft disk. To increase shine polish again after 3 - 4 hours. Always check that wood moisture is between 8% to 12%, and that the ambient temperature is between 15°C to 25°C and relative humidity not above 75%. Always use adequate individual protection devices. Always consult the technical and safety data sheet for the product.

NOTE

With buffer and disk: using a spatula distribute small amounts of wax over the entire floor. Avoid using too much product (max 10 - 20 gr/m²), which would make the surface tacky and hard to polish. PAVICERA SO can be applied warm to facilitate distribution, by heating using a water basin.