



ADHESIVES FOR CARPETING AND RESILIENT TEXTILE FLOORS



PELPREN 153

DOUBLE-COAT SOLVENT-BASED NEOPRENE ADHESIVE

All-purpose contact adhesive, ideal for bonding steps, skirting boards, various PVC profiles, rubber, carpeting, linoleum, cork, etc.

DO NOT USE:

- On solvent-sensitive materials
- Not suitable for expanding polystyrene

SURFACE PREPARATION:

The surfaces being bonded must be compact, dry and clean from loose particles such as oils, waxes, paint residues and dusts.

APPLICATION:

Allow the product to reach room temperature before use. Mix well before use. Apply the adhesive on both surfaces to be bonded, applying a thin layer with a paint brush or a fine-toothed steel spatula. Allow the adhesive to dry until it is no longer sticky to touch. Join the surfaces to be bonded together by pressing down hard from the centre towards the sides to release any air bubbles. Always check that wood moisture is between 8% to 12%, and that the ambient temperature is between 15°C to 25°C and relative humidity not above 75%. Always use adequate individual protection devices. Always consult the technical and safety data sheet for the product.

TECHNICAL CHARACTERISTICS:

Appearance:	Viscous liquid
Colour:	Amber
Viscosity (@20°C; Brookfield):	6000 - 7000
Yield (g/m ²):	150 - 180
Working life (minutes):	10 - 15
Usage temperature (°C):	+15 - +25
Ready for walking on (hours):	2 - 3
Film hardening (hours):	24 - 36 hours (depending on use and thickness applied)
Application/Equipment:	Fine-toothed spatula, paint brush
Equipment cleaning:	GR7 wash thinner, before the product sets
Storage (months): highest temperature +5°C	6
Disposal information	Dispose of in compliance with the local and national regulations in force
Packs	0.86 kg pots or 5 kg drums.
Usage limitations:	Inflammable. Ventilate the room when applying but avoid draughts. Allow the product to reach room temperature of 20°C before application. Spread across both surfaces to be bonded. Always use adequate individual protection devices.