



POLISH WB

MATT POLISH FOR VARNISHED PARQUET

Polish product used for maintaining pre-finished and laminate varnished wood floors.

TECHNICAL CHARACTERISTICS:

- Excellent revitalising power
- Quick drying
- **Matte/semi-matte finish**

WHERE IT CAN BE APPLIED:

- Pre-finished floors
- Varnished surfaces
- Laminates
- Flooring in PVC, LINOLEUM o LVT
- Marble or ceramic surfaces

DO NOT USE:

- Oiled floors
- Absorbent flooring or unfinished parquet

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Liquid
Viscosity, F 4 at 20 °C (seconds):	10 - 14
Yield: (g/m ²):	60 - 80
Drying time (minutes):	15 - 30
Usage temperature (°C):	+10 - +25
Application/Equipment:	Clean cloth
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	1-litre bottles – Boxes with 12 pieces
Usage limitations:	Spread evenly Do not apply in damp environments Do not use on absorbent cork or floors (unvarnished) Do not polish Allow the product to reach 20 °C before applying Frost sensitive Always consult the technical and safety information sheets Always use suitable personal protective equipment

SURFACE PREPARATION:

The surface must be varnished and cleaned thoroughly with a neutral wax remover (e.g. our PARQUETPRO product).

APPLICATION:

Product ready to use. Leave the product to reach room temperature before use.

Apply POLISH WB evenly with a damp cloth and leave to dry.

Avoid product accumulation. The product must be applied uniformly, avoiding rubbing or using excessive pressure on the surface.

NOTES:

Applying the product incorrectly may leave marks on the surface that can only be removed by using our DECERLEGNO wax remover.

HAZARD PICTOGRAMS:

-- -- --