



POLISH WB

MATT POLISH FOR VARNISHED PARQUET

Polish product used for maintaining prefinished and laminate varnished wood floors.

TECHNICAL CHARACTERISTICS:

- Excellent revitalising power
- Matt/semi-matt appearance
- Quick drying

WHERE IT CAN BE APPLIED:

- Pre-finished floors
- Varnished surfaces
- Laminates
- Flooring in PVC, LINOLEUM o LVT
- Marble or ceramic surfaces

DO NOT USE:

- Oiled floors
- Absorbent flooring or unfinished parquet

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Liquid
Viscosity (@20°C; Ford #4):	15 - 20
Yield (g/m ²):	60 - 80
Drying time (minutes):	15 - 30
Usage temperature (°C):	+10 - +25
Application/Equipment:	Clean cloth
Storage (months): temperature of between +5°C and +25°C	12
Disposal information	Dispose of in accordance with local and national legislation
Packaging:	1-litre bottles – Boxes with 12 pieces
Usage limitations:	Spread evenly Do not apply in damp environments Do not use on absorbent cork or floors (unvarnished) Do not polish Always use personal protective equipment Acclimatise the product at 20°C before applying Frost sensitive

PREPARING THE SURFACE

The surface must be varnished and cleaned thoroughly with a neutral wax remover (e.g. our PARQUETPRO product).

APPLICATION

Product ready to use. Leave the product to reach room temperature before use.

Apply POLISH WB evenly with a damp cloth and leave to dry.

Avoid product accumulation. The product must be applied uniformly, avoiding rubbing or using excessive pressure on the surface.

NOTE

Applying the product incorrectly may leave marks on the surface that can only be removed by using our DECERLEGNO wax remover.